

Ventilated Gastronorm Refrigeration


2/1 Gastronorm Capacity

BR1SS

BF2SS



BR models - suitable for fresh meat storage



FEATURES

- High grade 304 stainless steel exterior & interior
- Internal corners rounded to aid cleaning
- 4 adjustable shelves GN2/1 per door
- 60 mm thick insulation
- Lock fitted as standard
- Heavy duty castors as standard
- Single door models have reversible door
- LED lighting
- Self closing door(s) with dwell position
- Suitable for fresh meat storage (BR range)
- Replaceable door gasket

TECHNICAL SPECIFICATIONS

	BR models	BF models
Cooling:	Ventilated	
Controller:	Dixell controller	
Defrost:	Automatic	
Refrigerant:	R290	R290
Climate Class:	4	
Temperature Range:	-2°C ~ +8°C	-18°C ~ -22°C
Power Supply:	13amp	

MODEL	DOOR	GROSS CAPACITY	EXT. DIMENSIONS (H x W x D mm)	ENERGY RATING	POWER CONSUMPTION	KWH /ANNUM	DECIBELS	WEIGHT (kg)	RRP
BR1SS	1	650L	2010 x 740 x 830	C	215W	554	48dBA	136	
BF1SS	1	650L	2010 x 740 x 830	D	480W	2278	48dBA	141	
BR2SS	2	1300L	2010 x 1480 x 830	D	440W	1376	48dBA	213	
BF2SS	2	1300L	2010 x 1480 x 830	D	780W	4030	48dBA	226	

