turbofan

Technical data sheet for **EC40D10** ON THE SK40-10A STAND

Full Size 10 Tray Digital / Electric Combi Oven on a Stainless Steel Stand





Unit shall be a Blue Seal electrically heated Turbofan direct steam injection combination convection steam oven. The oven shall have a stainless steel oven chamber with 10 x 1/1 GN capacity, 14.5kW power rating and two 2 speed auto-reversing direction fans. Oven door shall be vented safe touch and feature LED oven chamber lighting. Electronic touch control panel shall provide cooking mode selection, 10 one touch favourite program keys, digital displays for temperature, time, humidity and programs, and a scrolling control knob for operation. Convection, Steam, and Combi cooking modes shall be usable in manual mode and program modes. Unit shall be optional core temp probe ready. Unit shall include as standard a self contained Automatic cleaning system with Liquid Clean System (LCS). A water hand shower shall be included as standard. Oven shall be able to be bench mounted on 100mm feet or mounted on Turbofan oven stand model SK40-10A. Unit shall be supplied in 100% recyclable shipping packaging.

SK40-10A

Unit shall be a Blue Seal Turbofan stainless steel oven stand. The stand shall be constructed from stainless steel tube with 4 adjustable feet. It shall be fitted with 6 tray runners suitable for 1/1 GN pans and 600 x 400 trays. The stand shall be fully compatible with, and support, Turbofan Combi Oven models EC40M10 and EC40D10. Unit shall be supplied in 100% recyclable shipping packaging.

STANDARD FEATURES

- Electric direct steam version
- 10 x 1/1 GN tray capacity
- 10 x 600mm x 400mm tray capacity
- · 70mm tray spacing
- · Compact 777mm wide
- 14kW heating power
- · 2 speed fan
- LED HVS (High Visibility System) alphanumeric display for temperature, Clima, time and core temperature
- 2.4" LCD-TFT colour display with rapid selection scroller knob for program and setting selection
- Over 95 preset recipe programs
- 99 free programs with up to 9 cycles in automatic sequence
- Manual cooking with three cooking modes Convection (50°C-260°C), Steam (50°C-130°C), Combi (50°C-260°C)
- Clima automatic measurement and control for humidity levels in the cooking chamber
- Manual pre-heating
- Auto reverse (automatic inversion of the direction of the fan) for perfectly uniform cooking
- · Automatic chamber venting control
- ECOVAPOR automatic control of the steam saturation in the cooking chamber
- ECOSPEED oven optimises and controls the delivery of energy to maintain correct cooking temperature
- · Core temperature probe ready
- USB connection
- Automatic LCS (Liquid Clean System) with Combi Clean liquid
- 7 automatic cleaning programs
- · Externally connected hand shower
- Timed LED chamber lighting
- Self-diagnostic operation check before and during use, with detailed description and audible fault warnings
- · Triple action water filter cartridge and filter head included

ACCESSORIES

- · Multipoint core temperature probe
- Turbofan SK40-10A Oven Stand



COMBI 40DSERIES EC40D10

turbofan

EC40D10 Full Size Digital/ Electric Combi Oven on a Stainless Steel Stand

Dimensions

Width	777mm
Depth	835mm
Height	1152mm
Weight	104kg
Packed Dimension	S
Width	910mm
Depth	865mm
Height	1265mm
Weight	117kg

 Weight
 II/kg

 Volume
 1.0 m³

 Shelves
 I/I GN
 I0

Shelf Spacings 70mm

Power connection requirements

Multi pole circuit breaker and all pole disconnection isolator switch installed near the appliance.

Electrical requirements

400-415V, 50Hz, 3P+N+E, 14.5kW, 20A/ph Water connection requirements

Water Supply

2 x R3/4 connections Cold Water Flow pressure 200-500 kPa Shut off valve with back flow prevention

Water Quality

- total hardness 60-90 ppm
- pH > 7.5
- Cl-(chloride) <30 ppm
 temperature < 50°C

Drain

- Funnel waste trap/tundish required
- 40 mm outlet
- Minimum fall/slope for waste 4°

SK40-10A Stainless Steel Stand

All stainless steel welded frame oven stand for Turbofan EC4010 tray Series Combi ovens 6 position tray runners 4 height adjustable feet Supplied CKD for assembly on site External Dimensions (SK40-10A Oven Stand) Width 810mm Height 697mm Depth 650mm Nett Weight (SK40-10A Oven Stand) 19kg

Packing Data (SK40-10A Oven Stand) 22kg

0.11m3 Width Height Depth

830mm 880mm 160mm

INSTALLATION CLEARANCES

Installation requirements (for precise installation instructions, please refer to the unit's installation manual). - rear 50mm

- rear - right

- left

50mm*

50mm*

*For recessed installations a minimum of 500mm clearance must be maintained on one of the sides. If heat sources are located near the Turbofan Combi, ensure that a minimum distance of 400mm is maintained.

Install in accordance with local body regulations only on horizontal surfaces and not against combustible walls.

OBLUE SEAL

EC40D10

blue-seal.co.uk turbofanoven.com

OM

40DSERIES

United Kingdom Blue Seal Limited Unit 67 Gravelly Business Park Gravelly Birmingham B24 8TQ England Telephone 0121-327 5575 Facsimile 0121-327 9711 sales@blue-seal.co.uk www.blue-seal.co.uk

Australia Moffat Pty Limited

740 Springvale Road Mulgrave, Victoria 3170 Australia Telephone 03-9518 3888 Facsimile 03-9518 3833 vsales@moffatcom.au www.moffatcom.au

New Zealand Moffat Limited


Christchurch 45 Illinois Drive Izone Business Hub Rolleston 7675 Telephone +64 3-983 6600 Facsimile +64 3-983 6660 sales@moffatco.nz www.moffatco.nz


Manufactured by: Moffat Limited 45 Illinois Drive, Izone Business Hub Rolleston 7675, New Zealand

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd UK.TNC.S.01.19







an Ali Group Company

