



## PRO-LITE

# LD46 Single Pan Freestanding Fryer

## Key features

- Integrated oil drainage system
  - Oil drainage bucket provided below pan
- Lift out control box at rear of fryer
  - Simple to remove for cleaning
- Supplied with lid as standard
  - Protects cooking oil when not in use
- Compact at only 300mm wide
  - Ideal for smaller, less demanding kitchens

## Accessories

- Additional basket

## Similar Models

- LD48 twin pan fryer
- LD50 countertop single pan fryer
- LD56 countertop twin pan fryer

## Specification *details*

Electrical rating (kW)	6
Electrical supply voltage	400V 2N~
Electrical current split (A)	L1: 13 L2: 13
Oil capacity (litres)	8
Chip output (kg/hour)	20
Weight (kg)	29
Packed weight (kg)	31
Dimensions (w x d x h - mm)	300 x 630 x 965
Packed dimensions (w x d x h - mm)	350 x 700 x 1100
GTIN number	5056466905798

## Installation notes

Adequate ventilation must be provided to supply sufficient fresh air for combustion and to allow easy removal of any such products that may present a risk to health. Please consult current legislation for details that relate to specific locations.

Install unit on a level, fireproof surface in a well-lit, draught free position. If floor is made of a combustible material, local fire requirements must be checked to ensure compliance.

A clearance of 150mm should be observed between appliance and any combustible wall.