



The Refrigeration Experts

## Product specification



### FFC4/2: 96 Ltr Counter Vari Temp Drawer

35-105

Variable temperature two drawer reduced width counter

## Features and benefits

- Lockable drawers provide maximum security
- Automatic hot gas defrost
- So simple to operate - change drawer temperature from fridge to freezer at the touch of a button
- High quality 304 grade stainless steel finish is food safe and hard wearing
- 2 x GN 1/1 150mm deep pan capacity per drawer maximises available storage space
- Fully removable robust drawer bins allow ease of cleaning
- Robust, heavy duty drawer runners can sustain up to 200kg in weight
- Supplied on roller castors as standard for ease of movement and positioning
- Works efficiently in hot kitchens, operating in ambient temperatures exceeding ISO Climate Class 5 (43°C ambient)
- This is a dual refrigeration system and requires two power supplies. Data about each system can be found in the spec table "Temperature" and "Temperature 2"

We use cookies to ensure you get the best experience on our website.

[More information.](#)

Accept all

Decline all

<b>Refrigerant</b>	R290
<b>Temperature</b>	Freezer -18/-21°C
<b>Electrical supply</b>	230/50/1
<b>Fuse rating (A)</b>	10
<b>Current (A)</b>	1.5
<b>Power (W)</b>	250
<b>Refrigerant mass (g)</b>	65
<b>Temperature 2</b>	Freezer -18/-21°C
<b>Fuse rating (A) 2</b>	10
<b>Current (A) 2</b>	1.5
<b>Power (w) 2</b>	250
<b>Refrigerant mass (g) 2</b>	65

<b>Finish ext/int</b>	304 S/S & 304 S/S
<b>Section configuration</b>	
<b>System</b>	Integral

<b>Height (mm)</b>	900
<b>Width (mm)</b>	775
<b>Depth (mm)</b>	700
<b>Gross volume (ltr)</b>	48
<b>Net volume (ltr)</b>	48
<b>Leg type</b>	Roller wheels
<b>Gross weight (kg)</b>	134.5
<b>Net weight (kg)</b>	126
<b>Gross volume (ltr) 2</b>	48

<b>Climate Class</b>	5
<b>Energy grade</b>	C
<b>EEI</b>	38.69
<b>AEC (kWh)</b>	1029
<b>Energy consumption (kWh/24hr)</b>	2.82
<b>GWP</b>	3
<b>Energy grade 2</b>	C
<b>EEI 2</b>	38.69
<b>AEC (kWh) 2</b>	1029
<b>Energy consumption (kWh/24hr) 2</b>	2.82

## Footnotes

- Adequate airflow must be kept around the counter: 150mm
- Ecodesign data relevant per compartment
- Add 20mm for depth if product is to be wall sited. Stopper required for air circulation – detachable if not wall sited.
- Accepts GN pans with a maximum depth of 150mm

We use cookies to ensure you get the best experience on our website.  
[More information.](#)

Accept all

Decline all

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU  
+44 (0)1553 691122 | [sales@foster-gamko.com](mailto:sales@foster-gamko.com) | [www.fosterrefrigerator.com](http://www.fosterrefrigerator.com)

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.

We use cookies to ensure you get the best experience on our website.  
[More information.](#)

Accept all

Decline all