

Sirman Spa Viale dell'Industria 9/11 35010 PIEVE DI CURTAROLO (PD), Italy Tel./Fax. +39 049 9698666 / +39 049 9698688 email: info@sirman.com



- Anodized cast aluminium alloy.
- Great distance between blade and motor for easy cleaning.

- Ventilated motor.
 Forged, hardened large thickness blades.
 Carriage running on self-lubricating bushes and lapped pins.
- Stainless steel screws and slice deflector.
- Strong thickness gauge support.

- Cast-in sharpener assembly.
 Compact dimensions and great cutting capacity.
 CE professional with device for releasing the carriage.
- Teflon coated or toothed blades are available on demand.
- 25? blade inclination.






More space between blade and body machine





Device for releasing tre carriage



Data sheet







Technical data

Model	Mirra 300 Y09
Blade	mm 300 - inch. 12
Motor	watt 210 / Hp 0,29
Cut thickness	mm 13
Run of carriage	mm 285
Hopper	mm 250x275
A	mm 435
В	mm 295
С	mm 600
D	mm 610
E	mm 420
F	mm 640
G	mm 510
L	mm 535
X	mm 250
Y	mm 185
H	mm 225
W	mm 210
Net weight	kg 20,5
Shipping	mm 800x600x520

Mirra: Mirra 300 Y09

Gross weight	kg 23,5
HS-CODE	84385000